

Economy 30



DATI TECNICI

- portata 30 litri/min • peso 5 Kg
- portagomma (nylon) Ø 40/50 mm



TECHNICAL DATA

- capacity 30 lt/min • weight 5 kg
- couplings (nylon) Ø 40/50 mm



Mini barile



DATI TECNICI

- portata 30 litri/min • peso 5 Kg
- portagomma (nylon) Ø 30 mm



TECHNICAL DATA

- capacity 30 lt/min • weight 5 kg
- couplings (nylon) Ø 30 mm



Le pompe a mano Fluxinos sono autoadescenti. La loro prevalenza totale è di 8 metri, sono interamente in acciaio inox stampato, le loro caratteristiche tecniche permettono alti rendimenti (da 40 a 120 lt/min) rispetto alle ridotte dimensioni e alla loro leggerezza (da 3 a 12 kg). La misura dei portagomma, in nylon o in acciaio inox, può variare da 30 a 50 mm. Inoltre i portagomma inox possono essere con filetto GAS Maschio diametro 1 1/2" o 2". Le membrane e le valvole delle pompe possono essere in neoprene, adatte a non alterare i liquidi pompati, o in elastomero speciale resistente ai carburanti. Permettono inoltre di operare con liquidi con grossi corpi solidi in sospensione senza danneggiare la pompa. Non hanno necessità di manutenzione e si puliscono facilmente. I modelli "Marina" sono pompe di sentina.

Fluxinos hand pumps are self-priming. Their overall prevalence is 8 meters, they are entirely in die-pressed stainless steel, and their technical features allow high yields (from 40 to 120 lt/min) compared to their small size and light weight (from 3 to 12 kg). The size of the hose connectors, in nylon or stainless steel, can be from 30 to 50 mm. In addition, the stainless steel hose connectors can be threaded GAS Male diam. 1 1/2 "or 2". The diaphragms and the pump valves may be made of neoprene, so as not to alter the pumped liquids, or of special fuel resistant elastomer. They can also operate with liquids with large solid bodies in suspension without damaging the pump. They require no maintenance and are easy to clean. The "Marina" models are bilge pumps.

solar

centrifugal

self-priming

manual

ball valves

accessories



stainless steel pumps

FLUXINOS

Jolly 300

DATI TECNICI

- portata 100/120 litri/min
- portagomma (nylon) Ø 40/50 mm
- peso 12 Kg

TECHNICAL DATA

- capacity 100/120 lt/min
- couplings (nylon) Ø 40/50 mm
- weight 12 kg



Jolly 300 marina

DATI TECNICI

- portata 100/120 litri/min
- portagomma (inox) Ø 40/50 mm
- peso 10 Kg

TECHNICAL DATA

- capacity 100/120 lt/min
- couplings (inox) Ø 40/50 mm
- weight 10 kg



Jolly Junior

DATI TECNICI

- portata 50/60 litri/min
- portagomma (nylon) Ø 30/40 mm
- peso 7 Kg

TECHNICAL DATA

- capacity 50/60 lt/min
- couplings (nylon) Ø 30/40 mm
- weight 7 kg



Jolly Junior marina

DATI TECNICI

- portata 50/60 litri/min
- portagomma (inox) Ø 30/40 mm
- peso 7 Kg

TECHNICAL DATA

- capacity 50/60 lt/min
- couplings (inox) Ø 30/40 mm
- weight 7 kg



Mini Jolly

DATI TECNICI

- portata 30/40 litri/min
- portagomma (nylon) Ø 30 mm
- peso 3 Kg

TECHNICAL DATA

- capacity 30/40 lt/min
- couplings (nylon) Ø 30 mm
- weight 3 kg



Mini Jolly marina

DATI TECNICI

- portata 30/40 litri/min
- portagomma (inox) Ø 30 mm
- peso 3 Kg

TECHNICAL DATA

- capacity 30/40 lt/min
- couplings (inox) Ø 30 mm
- weight 3 kg

