

_ SIMILAR TO _

	5	

U.S. EXPORT CLASSIFICATION: EAR99

THE SYMBOLS (X) , \hat{F} , \hat{P} and AMC denote features critical with respect to safety, function, process and alternate means of control. THESE FEATURES MUST BE CONTROLLED PER REQUIREMENTS OF THE "SUPPLIER QUALITY MANUAL" OR THE "OPERATIONS PROCESS CERTIFICATION STANDARD WORK".

	ENGINEERING	r comply with requirement(s) 5, C-283	Carrier A United Technologies Company	INDIANAPOLIS, IN. SYRACUSE, NY.
	THIRD ANGLE PROJECTION	UNITS METRIC mm	THIS DOCUMENT AND THE INFORMATION CONTA PROPRIETARY TO CARRIER CORPORATION AND OR DISCLOSED TO OTHERS, IN WHOLE OR IN THE WRITTEN AUTHORIZATION OF CARRIER CO	SHALL NOT BE USED PART, WITHOUT
	UNLESS OTHERWISE SPECIFIED DIMENSIONS TOLERANCES ARE: 0 DEC 1 DEC 2 DEC ANG			
	<u>±0</u> ±0.8 material SFF NOTFS	$\pm 0.25 \pm 1^{\circ}$	SWITCH	
	- -		ON/OFF drawing no. 346300-4	DWG REV
04/20	designer P.SAPPATI	created on 04/09/20	Sheet 1 of 1	_
DT	design engr S.MICHAEL	ITERATION	orig ecn no. 1131366	scale NONE
	<u>S.MICHAEL</u>			

All printed copies of this document are **UNCONTROLLED** copies.